

## Truck mixer AM-10E1.C.DO Technical Specification

<b>1</b>	<b>Model</b>	AM-10E1.C.DO
<b>2</b>	<b>Standard weight</b>	5050 kg
<b>3</b>	<b>Drum</b>	Type «C»
	Drum angle	10,5 deg
	Nominal capacity	10 m <sup>3</sup>
	Geometrical volume	16,4 m <sup>3</sup>
	Service hatch	2 on forward cone
	Rotation speed	0 - 14 rpm
	Shell thickness	5 mm low alloy carbon steel
	Blade thickness	5 mm low alloy carbon steel
	Bottom thickness	7 mm low alloy carbon steel
<b>4</b>	<b>Hydraulic pump drive</b>	DO - with PTO from truck
<b>5</b>	<b>Power consumption</b>	74 KW/100HP
<b>6</b>	<b>Hydraulic transmission</b>	EATON Pump and Motor Series 154
<b>7</b>	Optional	REXROTH Pump A4VTG71 / Motor AA2FM63
	<b>Control</b>	Mechanical cable control RPM control switch
<b>8</b>	<b>Drum gearbox</b>	ZF P4300
<b>9</b>	<b>Water system</b>	Water charging connection at two sides
	Powered by	Air pressure system from the truck
	<i>Optional</i>	<i>Drum gearbox driven water pump NST III</i>
	<b>Water tank capacity</b>	1000 L
<b>10</b>	<b>Accessories standard</b>	Reinforced charging hopper with rubber extension
		Reinforced discharge shell
		Reinforced discharge rotary chute
		Mudguards with flaps
		Washing hose
		Extension chute with supports and clamp
	<b>Painting</b>	WHITE